

GPON OLT 16 PON PORTS

GPON OLT 16 PON PORTS 1U 19 inch HAAFH - 16*PON+4*GE COMO+2*10GE(SFP+)



1U 19 inch
1+1power redundancy
16* fixed GPON port

4*GE COMBO port
2*10GE SFP+ port
1*console port

Applications

This model of 16 PON PORTS GPON OLT is a new product designed by superlink, a small-capacity cassette GPON OLT, meeting the requirements of ITU-T G.984/G.988 and relative standards of China Telecom/Unicom GPON, with super GPON access capacity, carrier-class reliability and the complete security function. It can satisfy long-distance optical fiber access requirement on account of its excellent management, maintenance and monitoring capability, abundant service features and flexible network mode. GPON OLT 16PON can be used with network management system so as to provide users with the comprehensive access and perfect solution.

It provides 16 * downlink GPON port, 4 *GE combo port and 2* 10G SFP+ port for uplink. The height is only 1U for easy installation and space saving. GPON OLT 16PON is suitable for Broadcast three in one, video surveillance network, enterprise LAN, Internet of Things, etc.

GPON OLT 16 PON PORTS

Features

- PON ITU-TG.984.x standard
 - Maximum 20 Km PON transmission distance
 - access 128 terminals for single fiber PON
 - Uplink and downlink triple churning encrypted function with 128Bits
 - ONU terminal legitimacy certification, report illegal ONU registration
 - DBA algorithm, the particle is 1Kbit/s
 - Standard OMCI management function
 - ONU batch software upgrade, fixed time upgrade, real time upgrade
 - PON port optical power detection
- L2 Features MAC MAC Black Hole
 - Port MAC Limit
 - 64K MAC (packet exchange chip cache 2MB, external cache 720 MB)
- L2 Features VLAN 4K VLAN entries
 - Port-based/MAC-based/protocol/IP subnet-based
 - QinQ and flexible QinQ (StackedVLAN)
 - VLAN Swap and VLAN Remark
 - PVLAN to realize port isolation and saving public-vlan resources
 - GVRP
- L2 Features Spanning Tree STP/RSTP/MSTP
 - Remote loop detecting
- L2 Features Port Bi-directional bandwidth control
 - Static link aggregation and LACP(Link Aggregation Control Protocol)
 - Port mirroring
- Security Features User's Security Anti-ARP-spoofing
 - Anti-ARP-flooding
 - IP Source Guard create IP+VLAN+MAC+Port binding
 - Port Isolation
 - MAC address binding to the port and MAC address filtering
 - IEEE 802.1x and AAA/Radius authentication
- Security Features Device Security Anti-DOS attack(such as ARP, Synflood, Smurf, ICMP attack), ARP detection, worm and Msblaster worm attack
 - SSHv2 Secure Shell
 - SNMP v3 encrypted management
 - Security IP login through Telnet
 - Hierarchical management and password protection of users
- Security Features Network Security User-based MAC and ARP traffic examination
 - Restrict ARP traffic of each user and force-out user with abnormal ARP traffic
 - Dynamic ARP table-based binding
 - IP+VLAN+MAC+Port binding
 - L2 to L7 ACL flow filtration mechanism on the 80 bytes of the head of user-defined packet
 - Port-based broadcast/multicast suppression and auto-shutdown risk port
 - URPF to prevent IP address counterfeit and attack
 - DHCP Option82 and PPPoE+ upload user's physical location Plaintext authentication of OSPF, RIPv2 and BGPv4 packets and MD5
 - cryptograph authentication

GPON OLT 16 PON PORTS

- Service Features ACL Standard and extended ACL
Time Range ACL
Flow classification and flow definition based on source/destination MAC address, VLAN, 802.1p, ToS, DiffServ, source/destination IP(IPv4/IPv6) address, TCP/UDP port number, protocol type, etc
packet filtration of L2~L7 deep to 80 bytes of IP packet head
- Service Features QoS Rate-limit to packet sending/receiving speed of port or self-defined flow and provide general flow monitor and two-speed tri-color monitor of self-defined flow
Priority remark to port or self-defined flow and provide 802.1P, DSCP priority and Remark
CAR(Committed Access Rate), Traffic Shaping and flow statistics
Packet mirror and redirection of interface and self-defined flow
Super queue scheduler based on port or self-defined flow. Each port/flow supports 8 priority queues and scheduler of SP, WRR and SP+WRR.
Congestion avoid mechanism, including Tail-Drop and WRED
- Service Features IPv4 ARP Proxy
DHCP Relay
DHCP Server
Static Routing
RIPv1/v2
OSPFv2
ECMP
PBR
- Service Features Multicast
IGMPv1/v2/v3
IGMPv1/v2/v3 Snooping
IGMP Filter
MVR and cross VLAN multicast copy
IGMP Fast leave
IGMP Proxy
PIM-SM/PIM-DM/PIM-SSM
MLDv2/MLDv2 Snooping
- Reliability Loop Protection ERPP or ERPS Loopback-detection
- Reliability Link Protection FlexLink (recover-time <50ms)
RSTP/MSTP (recover-time <1s)
LACP (recover-time <10ms)
BFD
- Reliability Device Protection VRRP host backup 1+1 power hot backup
- Maintenance Network Maintenance Port real-time, utilization and transmit/receive statistic based on Telnet
RFC3176 sFlow analysis
LLDP
GPON OMCI
RFC 3164 BSD syslog Protocol
Ping and Traceroute
- Maintenance Device Management
CLI, Console port, Telnet and WEB
SNMPv1/v2/v3
RMON (Remote Monitoring)1,2,3,9 groups MIB
NTP
network management

GPON OLT 16 PON PORTS

Detailed product specifications

1.Parameters

PON standard.	GPON ITU-T G.984.x
Service Port	16*PON, 4*GE COMBO, 2*10GE SFP+, double AC/DC power supply
Redundancy Design	Dual power supply Support AC input, double DC input and AC+DC input
Power Supply	AC: input 90~264V 47/63Hz; DC: input -36V~-72V;
Power Consumption	≤110W
Dimensions (Width x Height x Depth)	440mm×44mm×410mm
Weight (Full-Loaded)	≤7.5kg
Environmental Requirements	Working temperature: -10°C~55°C Storage temperature: -40C~70C Relative humidity: 10%~90%, non-condensing

2.Shipping packaging

Data of packaging	1pcs /ctn,7kg/ctn,575*500*115mm 5pcs /ctn,35kg/ctn,645*597*525mm
-------------------	---

GPON OLT 16 PON PORTS

3.Detail Panel

